



504.1683

PRESA INTERBLOCCATA

16A 2P+T 6h 200-250V 50Hz 60Hz II 2GD
130X260MM_PAR Con interblocco meccanico

Certificati

| TECHDATA | | NORME E LEGGI | |
|------------------------------|--------------------------------|----------------------|---|
| Tipologia prodotto | PRESA INTERBLOCCATA | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Serie commerciale | Serie ADVANCE-GRP[GD] | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica | PRESA INTERBLOCCATA | | |
| Tipo installazione | PARETE | | |
| Corrente nominale | 16A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Poli | 2P+T | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Riferimento Orario | 6h | | |
| Tensione nominale (range) | 200-250V | EN 60309-4 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock |
| Tensione nominale | 200-250V | | |
| Frequenza d'impiego | 50Hz | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Frequenza d'impiego | 60Hz | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Colore | BLU | | |
| Materiale | GRP Glass Reinforced Polyester | EN 60309-4/A1 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock |
| Grado di protezione generico | Protetto da getti d'acqua | | |
| Grado di protezione IP | IP66 | EN 60079-0 (2012) | [European Standard] Explosive atmospheres. General requirements. |
| Flangia | 130X260MM_PAR | IEC 60079-0 (2011) | [International Standard] Electrical Apparatus for Explosive Gas Atmospheres - Part 0: General Requirements. |
| Uscita cavo | 1xM25 | | |
| Gruppo e categorie EX | II 2GD | EN 60079-31 (2014) | [European Standard] Explosive atmospheres. Equipment dust ignition |

| | | | |
|-----------------------------|---------------------------|---------------------------|---|
| Temperatura ambiente Ta min | -35 °C | IEC 60079-31 (2013) | protection by enclosure "t" [International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t" |
| Temperatura ambiente Ta max | 60 °C | EN 60079-0/A11 (2013) | [European Standard] Explosive atmospheres. General requirements. |
| Opzioni | Con interblocco meccanico | EN 60079-1 (2014) | [European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd' |
| Lucchetto | ø5mm | EN 60079-7 (2015) | [European Standard] Explosive atmospheres. Equipment protection by increased safety "e" |
| | | IEC 60079-1 (2014) | [International Standard] Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d". |
| | | IEC 60079-7 (2015) | [International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e". |
| | | DIRECTIVE ATEX 2014/34/UE | [European Directives] Atmosphere Explosive |