


Accessori Accessories

Riduzioni 6016 Reductions 6016



**Tipo A
Type A**



In conformità a tutti i raccordi filettati per tubi rigidi o pieghevoli. Sono utilizzate quando è necessario realizzare accoppiamenti tra imbrocci filettati diversi, sia per diametro che per tipo di filettatura.

Sono prodotte in ottone, nichelate successivamente per conferire una migliore resistenza alle avverse condizioni ambientali in cui saranno utilizzate. Continuità elettrica garantita

Gli articoli con un Ø nella colonna CH sono privi di esagono.

Filettature

- Metrico ISO CEI EN 60423
- GAS cilindrico UNI ISO 228
- PG secondo DIN 40430.

In accordance with all threaded fittings for rigid or flexible conduits.

They are used when it is necessary to realize couplings between different threaded inlets, both for diameter and for type of thread.

Made in brass, subsequently nickel plated to confer a better resistance to adverse environmental conditions where they will be used.

Electrical continuity guaranteed

Parts with a Ø in the column CH are without hexagon.

Threads


- ISO Metric IEC EN 60423
- UNI ISO 228 GAS cylindrical
- PG in accordance with DIN 40430

Metrico - Metrico Metric - Metric

| CODICE CODE | DIMENSIONI mm DIMENSIONS mm | | | | | TIPO TYPE | CONFEZIONE PACKAGE pz / pcs. |
|----------------|--------------------------------|---------|----|-----|-----|--------------|------------------------------------|
| | F1 m | F2 f | CH | LF2 | LF1 | | |
| 6016-1620 | M16x1,5 | M20x1,5 | 22 | 11 | 8 | B | 20 |
| 6016-2016 | M20x1,5 | M16x1,5 | 24 | 12 | 8 | A | 20 |
| 6016-2025 | M20x1,5 | M25x1,5 | 28 | 11 | 8 | B | 10 |
| 6016-2520 | M25x1,5 | M20x1,5 | 26 | 14 | 10 | A | 20 |
| 6016-2532 | M25x1,5 | M32x1,5 | 35 | 13 | 10 | B | 10 |
| 6016-3220 | M32x1,5 | M20x1,5 | 35 | 14 | 10 | A | 10 |
| 6016-3225 | M32x1,5 | M25x1,5 | 35 | 14 | 10 | A | 10 |
| 6016-3240 | M32x1,5 | M40x1,5 | 42 | 13 | 10 | B | 10 |
| 6016-4020 | M40x1,5 | M20x1,5 | 42 | 18 | 13 | A | 10 |
| 6016-4025 | M40x1,5 | M25x1,5 | 42 | 18 | 13 | A | 10 |
| 6016-4032 | M40x1,5 | M32x1,5 | 42 | 18 | 13 | A | 10 |
| 6016-4050 | M40x1,5 | M50x1,5 | 55 | 14 | 12 | B | 5 |
| 6016-5032 | M50x1,5 | M32x1,5 | 50 | 19 | 13 | A | 10 |
| 6016-5040 | M50x1,5 | M40x1,5 | 50 | 19 | 13 | A | 5 |
| 6016-5063 | M50x1,5 | M63x1,5 | 65 | 18 | 13 | B | 1 |
| 6016-6340 | M63x1,5 | M40x1,5 | 65 | 21 | 14 | A | 2 |
| 6016-6350 | M63x1,5 | M50x1,5 | 65 | 21 | 14 | A | 2 |



**Tipo B
Type B**



Accessori Accessories

Riduzioni 6019 - 6105 Reductions 6019 - 6105

Metrico - GAS ISO 228 Metric - GAS ISO 228

| CODICE CODE | DIMENSIONI mm DIMENSIONS mm | | | | | TIPO TYPE | CONFEZIONE PACKAGE pz / pcs. |
|----------------|--------------------------------|------|----|------|-----|--------------|------------------------------------|
| | F1 m | F2 f | CH | LF2 | LF1 | | |
| 6019-1638 | M16x1,5 | 3/8" | 18 | 11,0 | 8 | B | 10 |
| 6019-2012 | M20x1,5 | 1/2" | 24 | 11,0 | 8 | B | 20 |
| 6019-2534 | M25x1,5 | 3/4" | 30 | 12,5 | 10 | B | 10 |
| 6019-2538 | M25x1,5 | 3/8" | 26 | 14,0 | 10 | A | 10 |
| 6019-3201 | M32x1,5 | 1" | 35 | 13,0 | 10 | B | 10 |
| 6019-6302 | M63x1,5 | 2" | 65 | 19,0 | 15 | B | 2 |

Metrico - PG Metric - PG

| CODICE CODE | DIMENSIONI mm DIMENSIONS mm | | | | | TIPO TYPE | CONFEZIONE PACKAGE pz / pcs. |
|----------------|--------------------------------|------|------|-----|-----|--------------|------------------------------------|
| | F1 m | F2 f | CH | LF2 | LF1 | | |
| 6105-1609 | M16x1,5 | 9 | ø 20 | 9 | 9 | B | 10 |
| 6105-1611 | M16x1,5 | 11 | ø 22 | 9 | 9 | B | 10 |
| 6105-2011 | M20x1,5 | 11 | ø 23 | 9 | 9 | B | 10 |
| 6105-2013 | M20x1,5 | 13,5 | 24 | 9 | 9 | B | 10 |
| 6105-2516 | M25x1,5 | 16 | ø 27 | 9 | 9 | B | 10 |
| 6105-3221 | M32x1,5 | 21 | 35 | 14 | 14 | A | 10 |
| 6105-4029 | M40x1,5 | 29 | 42 | 18 | 18 | A | 5 |
| 6105-5036 | M50x1,5 | 36 | 50 | 15 | 15 | B | 5 |
| 6105-6348 | M63x1,5 | 48 | 65 | 15 | 15 | B | 2 |

GAS ISO 228 - Metrico GAS ISO 228 - Metric

| CODICE CODE | DIMENSIONI mm DIMENSIONS mm | | | | | TIPO TYPE | CONFEZIONE PACKAGE pz / pcs. |
|----------------|--------------------------------|---------|------|------|------|--------------|------------------------------------|
| | F1 m | F2 f | CH | LF2 | LF1 | | |
| 6019-1216 | 1/2" | M16x1,5 | 24 | 13,0 | 9,5 | A | 50 |
| 6019-3420 | 3/4" | M20x1,5 | 28 | 13,5 | 9,5 | A | 20 |
| 6019-0125 | 1" | M20x1,5 | 35 | 15,5 | 10,5 | A | 10 |
| 6019-0120 | 1" | M25x1,5 | 35 | 15,5 | 10,5 | A | 10 |
| 6019-0132 | 1" | M32x1,5 | 35 | 11,0 | 14,0 | B | 10 |
| 6019-11432 | 1" 1/4 | M32x1,5 | 42 | 19,0 | 14,0 | A | 10 |
| 6019-11240 | 1" 1/2 | M40x1,5 | 50 | 19,0 | 14,0 | A | 10 |
| 6019-0250 | 2" | M50x1,5 | 60 | 26,5 | 20,0 | A | 10 |
| 6019-0263 | 2" | M63x1,5 | 65 | 20,0 | 18,0 | B | 10 |
| 6019-21263* | 2" 1/2 | M63x1,5 | ø 75 | 31,0 | 19,0 | A | 1 |


*In alluminio
*In aluminium

■ Accessori Accessories


Riduzioni 6054 Reductions 6054



Tipo A
Type A



Tipo B
Type B



GAS ISO 228 - PG GAS ISO 228 - PG

| CODICE CODE | DIMENSIONI mm DIMENSIONS mm | | | | | TIPO TYPE | CONFEZIONE PACKAGE pz / pcs. |
|----------------|--------------------------------|------|------|------|------|--------------|------------------------------------|
| | F1 m | F2 f | CH | LF2 | LF1 | | |
| 6054-0409 | 1/4" | 9 | 18 | 10,0 | 8,0 | B | 10 |
| 6054-0411 | 1/4" | 11 | 22 | 11,0 | 8,0 | B | 20 |
| 6054-0413 | 1/4" | 13,5 | 24 | 11,0 | 8,0 | B | 20 |
| 6054-3809 | 3/8" | 9 | 22 | 10,0 | 9,5 | B | 20 |
| 6054-3811 | 3/8" | 11 | 22 | 9,5 | 9,0 | B | 20 |
| 6054-3813 | 3/8" | 13,5 | 24 | 11,0 | 9,5 | B | 20 |
| 6054-3816 | 3/8" | 16 | 24 | 9,5 | 9,0 | B | 20 |
| 6054-1209 | 1/2" | 9 | 24 | 13,5 | 9,5 | A | 10 |
| 6054-1211 | 1/2" | 11 | 24 | 9,5 | 9,0 | B | 20 |
| 6054-1213 | 1/2" | 13,5 | 24 | 11,0 | 9,5 | B | 20 |
| 6054-1216 | 1/2" | 16 | 24 | 11,0 | 9,5 | B | 20 |
| 6054-1221 | 1/2" | 21 | 30 | 12,0 | 9,5 | B | 20 |
| 6054-3411 | 3/4" | 11 | 28 | 13,5 | 9,5 | A | 10 |
| 6054-3413 | 3/4" | 13,5 | 28 | 13,5 | 9,5 | A | 10 |
| 6054-3416 | 3/4" | 16 | 28 | 13,5 | 9,5 | A | 10 |
| 6054-3421 | 3/4" | 21 | 30 | 12,0 | 9,5 | B | 10 |
| 6054-3429 | 3/4" | 29 | 40 | 13,0 | 11,0 | B | 10 |
| 6054-0111 | 1" | 11 | 35 | 15,5 | 10,5 | A | 10 |
| 6054-0113 | 1" | 13,5 | 35 | 15,5 | 10,5 | A | 10 |
| 6054-0116 | 1" | 16 | 35 | 15,5 | 10,5 | A | 10 |
| 6054-0121 | 1" | 21 | 35 | 15,5 | 10,5 | A | 10 |
| 6054-0129 | 1" | 29 | 42 | 14,0 | 12,0 | B | 10 |
| 6054-11421 | 1" 1/4 | 21 | 45 | 19,0 | 13,0 | A | 5 |
| 6054-11436 | 1" 1/4 | 36 | ø 50 | 16,0 | 14,0 | B | 10 |
| 6054-11236 | 1" 1/2 | 36 | ø 55 | 16,0 | 14,0 | B | 5 |

Riduzioni 6004
Reductions 6004

GAS ISO 228 - GAS ISO 228
GAS ISO 228 - GAS ISO 228

| CODICE CODE | DIMENSIONI mm DIMENSIONS mm | | | | | TIPO TYPE | CONFEZIONE PACKAGE pz / pcs. |
|----------------|--------------------------------|--------|------|------|------|--------------|------------------------------------|
| | F1 m | F2 f | CH | LF2 | LF1 | | |
| 6004-0438 | 1/4" | 3/8" | 18 | 11,0 | 8,0 | B | 10 |
| 6004-0412 | 1/4" | 1/2" | 24 | 11,0 | 8,0 | B | 10 |
| 6004-0434 | 1/4" | 3/4" | 30 | 12,0 | 7,0 | B | 10 |
| 6004-3804 | 3/8" | 1/4" | 22 | 13,0 | 9,5 | A | 20 |
| 6004-3812 | 3/8" | 1/2" | 24 | 11,0 | 9,5 | B | 20 |
| 6004-3834 | 3/8" | 3/4" | 28 | 12,5 | 9,5 | B | 10 |
| 6004-1204 | 1/2" | 1/4" | 24 | 13,0 | 9,5 | A | 20 |
| 6004-16 | 1/2" | 3/8" | 24 | 13,0 | 9,5 | A | 50 |
| 6004-1234 | 1/2" | 3/4" | 28 | 12,5 | 9,5 | B | 10 |
| 6004-1201 | 1/2" | 1" | 38 | 10,0 | 13,0 | B | 5 |
| 6004-3438 | 3/4" | 3/8" | 28 | 13,5 | 9,5 | A | 20 |
| 6004-3412 | 3/4" | 1/2" | 28 | 13,5 | 9,5 | A | 20 |
| 6004-3401 | 3/4" | 1" | 35 | 13,0 | 9,5 | B | 10 |
| 6004-138 | 1" | 3/8" | 35 | 15,5 | 10,5 | A | 10 |
| 6004-112 | 1" | 1/2" | 35 | 15,5 | 10,5 | A | 10 |
| 6004-134 | 1" | 3/4" | 35 | 15,5 | 10,5 | A | 10 |
| 6004-1114 | 1" | 1" 1/4 | ø 50 | 18,0 | 14,0 | B | 5 |
| 6004-1112 | 1" | 1" 1/2 | 50 | 19,0 | 14,0 | B | 5 |
| 6004-11438* | 1" 1/4 | 3/8" | 42 | 24,0 | 15,0 | A | 10 |
| 6004-11412 | 1" 1/4 | 1/2" | 42 | 22,0 | 15,0 | A | 10 |
| 6004-11434* | 1" 1/4 | 3/4" | 42 | 23,0 | 15,0 | A | 10 |
| 6004-1141* | 1" 1/4 | 1" | 42 | 23,0 | 15,0 | A | 5 |
| 6004-1412 | 1" 1/4 | 1" 1/2 | 50 | 15,0 | 16,0 | B | 5 |
| 6004-11238* | 1" 1/2 | 3/8" | 50 | 25,0 | 17,0 | A | 10 |
| 6004-11212 | 1" 1/2 | 1/2" | 50 | 25,0 | 17,5 | A | 5 |
| 6004-11234 | 1" 1/2 | 3/4" | 50 | 25,0 | 17,5 | A | 5 |
| 6004-1121 | 1" 1/2 | 1" | 50 | 21,0 | 15,0 | A | 5 |
| 6004-1214* | 1" 1/2 | 1" 1/4 | 50 | 25,0 | 17,0 | A | 5 |
| 6004-11202 | 1" 1/2 | 2" | ø 65 | 19,0 | 16,5 | B | 10 |
| 6004-0234* | 2" | 3/4" | 60 | 27,0 | 20,0 | A | 5 |
| 6004-21* | 2" | 1" | 60 | 27,0 | 20,0 | A | 5 |
| 6004-2114 | 2" | 1" 1/4 | 60 | 27,0 | 20,0 | A | 10 |
| 6004-2112* | 2" | 1" 1/2 | 60 | 27,0 | 20,0 | A | 5 |


* Prodotti in acciaio zincato
* Made of galvanized steel

■ Accessori Accessories


Riduzioni 6104 Reductions 6104



Tipo A
Type A



Tipo B
Type B



PG - PG PG - PG

| CODICE CODE | DIMENSIONI mm DIMENSIONS mm | | | | | TIPO TYPE | CONFEZIONE PACKAGE pz / pcs. |
|----------------|--------------------------------|------|-----|------|------|--------------|------------------------------------|
| | F1 m | F2 f | CH | LF2 | LF1 | | |
| 6104-0709 | 07 | 09 | ø18 | 10,0 | 5,0 | B | 10 |
| 6104-0907 | 09 | 07 | 18 | 8,0 | 5,0 | A | 10 |
| 6104-0911 | 09 | 11 | ø20 | 9,5 | 6,0 | B | 10 |
| 6104-0913 | 09 | 13,5 | ø23 | 10,5 | 6,0 | B | 10 |
| 6104-1107 | 11 | 07 | 19 | 9,0 | 6,0 | A | 10 |
| 6104-1109 | 11 | 09 | 19 | 9,0 | 6,0 | A | 10 |
| 6104-1113 | 11 | 13,5 | ø23 | 10,5 | 6,0 | B | 10 |
| 6104-1116 | 11 | 16 | ø27 | 11,5 | 6,0 | B | 10 |
| 6104-1309 | 13,5 | 09 | 22 | 9,0 | 6,0 | A | 10 |
| 6104-1311 | 13,5 | 11 | 22 | 9,0 | 6,0 | A | 10 |
| 6104-1316 | 13,5 | 16 | 27 | 11,5 | 6,5 | B | 20 |
| 6104-1321 | 13,5 | 21 | ø31 | 13,0 | 6,5 | B | 10 |
| 6104-1607 | 16 | 07 | 23 | 10,0 | 7,0 | A | 10 |
| 6104-1609 | 16 | 09 | 24 | 10,5 | 6,5 | A | 10 |
| 6104-1611 | 16 | 11 | 24 | 9,0 | 6,0 | A | 10 |
| 6104-1613 | 16 | 13,5 | 24 | 9,0 | 6,0 | A | 10 |
| 6104-1621 | 16 | 21 | 30 | 13,0 | 6,5 | B | 10 |
| 6104-2113 | 21 | 13,5 | 30 | 10,0 | 7,0 | A | 10 |
| 6104-2116 | 21 | 16 | 30 | 10,0 | 7,0 | A | 10 |
| 6104-2129 | 21 | 29 | 42 | 13,0 | 7,0 | B | 10 |
| 6104-2921 | 29 | 21 | 42 | 11,0 | 7,5 | A | 20 |
| 6104-2936 | 29 | 36 | 50 | 12,0 | 10,5 | B | 5 |
| 6104-3629 | 36 | 29 | 50 | 12,0 | 8,5 | A | 5 |
| 6104-4236 | 42 | 36 | 58 | 15,0 | 11,0 | A | 5 |
| 6104-4248 | 42 | 48 | 63 | 23,0 | 10,0 | B | 5 |
| 6104-4842 | 48 | 42 | 60 | 14,0 | 10,0 | A | 5 |

■ Accessori Accessories

Riduzioni 6054 Reductions 6054

PG - GAS ISO 228 PG - GAS ISO 228

| CODICE CODE | DIMENSIONI mm DIMENSIONS mm | | | | | TIPO TYPE | CONFEZIONE PACKAGE pz / pcs. |
|----------------|--------------------------------|--------|----|------|------|--------------|------------------------------------|
| | F1 m | F2 f | CH | LF2 | LF1 | | |
| 6054-0704 | 07 | 1/4" | 18 | 11,0 | 9,0 | B | 20 |
| 6054-0738 | 07 | 3/8" | 18 | 11,0 | 9,0 | B | 20 |
| 6054-0904 | 09 | 1/4" | 18 | 11,0 | 9,0 | B | 20 |
| 6054-0938 | 09 | 3/8" | 19 | 9,0 | 9,0 | B | 20 |
| 6054-0912 | 09 | 1/2" | 24 | 12,0 | 7,0 | B | 10 |
| 6054-1104 | 11 | 1/4" | 22 | 11,5 | 7,0 | A | 20 |
| 6054-1138 | 11 | 3/8" | 22 | 11,0 | 9,0 | B | 20 |
| 6054-1112 | 11 | 1/2" | 24 | 11,0 | 9,0 | B | 20 |
| 6054-1304 | 13,5 | 1/4" | 22 | 11,5 | 7,5 | A | 20 |
| 6054-1338 | 13,5 | 3/8" | 24 | 11,5 | 7,5 | A | 20 |
| 6054-1312 | 13,5 | 1/2" | 24 | 11,0 | 9,0 | B | 20 |
| 6054-1334 | 13,5 | 3/4" | 30 | 12,5 | 9,0 | B | 10 |
| 6054-1604 | 16 | 1/4" | 24 | 11,5 | 7,5 | A | 20 |
| 6054-1638 | 16 | 3/8" | 24 | 11,5 | 7,5 | A | 20 |
| 6054-1612 | 16 | 1/2" | 24 | 11,0 | 7,0 | B | 20 |
| 6054-1634 | 16 | 3/4" | 30 | 12,5 | 7,0 | B | 10 |
| 6054-2138 | 21 | 3/8" | 30 | 11,5 | 7,5 | A | 20 |
| 6054-2112 | 21 | 1/2" | 30 | 11,5 | 7,5 | A | 20 |
| 6054-2134 | 21 | 3/4" | 30 | 12,5 | 7,0 | B | 10 |
| 6054-2101 | 21 | 1" | 35 | 12,5 | 7,0 | B | 10 |
| 6054-2934 | 29 | 3/4" | 42 | 13,0 | 8,0 | A | 10 |
| 6054-2901 | 29 | 1" | 39 | 15,0 | 10,0 | A | 10 |
| 6054-29114 | 29 | 1" 1/4 | 42 | 15,0 | 10,5 | B | 5 |
| 6054-36114 | 36 | 1" 1/4 | 50 | 17,5 | 11,5 | A | 5 |
| 6054-36112 | 36 | 1" 1/2 | 50 | 16,0 | 14,0 | B | 5 |
| 6054-42114 | 42 | 1" 1/4 | 58 | 18,0 | 12,0 | A | 5 |
| 6054-42112 | 42 | 1" 1/2 | 58 | 18,0 | 12,0 | A | 5 |