


## ■ Raccordi a innesto rapido in acciaio inox AISI 316L AISI 316L stainless steel quick coupling fittings

### Tubo - Filetto femmina 6112-XX

### Conduit - Female thread 6112-XX



#### Filettatura Metrica Metric thread

CODICE CODE	DIAMETRO NOMINALE NOMINAL DIAMETER		DIMENSIONI mm DIMENSIONS mm					CONFEZIONE PACKAGE
	ØD mm	F	ØPU	CH	LF	D	L	pz / pcs.
6112-16XX	16	M16x1,5	14,5	21	10	24	43	8
6112-20XX	20	M20x1,5	18,5	25	10	28	43	8
6112-25XX	25	M25x1,5	23,5	30	10	32	43	5
6112-32XX	32	M32x1,5	30,5	37	12	39	46	4
6112-40XX	40	M40x1,5	38,5	47	15	50	58,5	5
6112-50XX	50	M50x1,5	48,5	56	15	60	58,5	5
6112-63XX	63	M63x1,5	57	Ø74,5	21,5	75	71,5	1



IP66  
IP68  
IP69

CEI EN 61386




CEI EN 61386




### Tubo rigido - Tubo flessibile 6117-XX

### Rigid Conduit - Flexible conduit 6117-XX



CODICE CODE	DIAMETRO NOMINALE NOMINAL DIAMETER	TUBO FLESSIBILE FLEXIBLE CONDUIT	DIMENSIONI mm DIMENSIONS mm			CONFEZIONE PACKAGE	
	Ød mm		ØPU	CH1	CH2	D	pz / pcs.
6117XX20N	20	16	13,8	30	30	33	25
6117XX25N	25	21	18,0	36	36	40	15
6117XX32N	32	27	24,0	46	46	50	10
6117XX4035	40	35	32,0	55	50	55	5
6117XX5040	50	40	38,0	60	60	64	5
6117XX63N	63	51	48	74	Ø74,5	75	1



IP66  
IP68  
IP69

CEI EN 61386



CEI EN 61386

