



Scotchcast™

REACH
1907/2007/EC


Resin Kits 92-NBA 0 up to 92-NBA 7 Inline Joint Kit Series with Resin 40

Application

3M™ Scotchcast™ resin joint kits 92-NBA x are designed to be used for 1-core up to 5-core non shielded, polymeric, low voltage energy cables. The application incorporates electrical insulation and mechanical protection of joints with compression or mechanical connectors. They can be used for indoor and outdoor, underground and submerged applications.

Features

- Resin 40 in transparent two chamber bags with integrated Closed Mixing and Pouring (CMP) system.
- One part Mould Body with Snap Fit closing system for quick and easy handling.
- Transparent Mould Body for easy control of connector distances in the joint.
- Web spacer for 4-core cable application to ensure the distance between connectors available for the sizes NBA 1 up to NBA 4.
- Pre cut foam sealing elements to provide reliable sealing to the Mould Body without tooling for all cable application diameters.
- Closure cap to prevent any pollution.



Kit content

- Transparent mould body with closure cap
- Scotchcast™ 40 resin bag with CMP
- Pre-cut sealing elements
- Web spacer elements
- Abrasive sponge
- Detailed instruction

Product Description

3M™ Scotchcast™ resin inline joint kit will be delivered with a one part transparent mould body for simple and easy handling. Distances inside the body can be checked easily. All necessary dimensions, like application range, cable preparation are given in the detailed instruction.

The two foam sealing elements can be adapted to the required cable diameter by removing the pre-cut adapter rings.

A web spacer ensures the minimum required distance to each connector. It can be applied for 3-core and 4-core cables.

The resin 40 is delivered in two chamber bag with integrated spout and aluminium Guard Bag for protection against humidity.

The reopenable seam and integrated spout with a membrane does provide a Closed, Mixing and Pouring system.





After the seam of the two chamber bag was opened, the resin components can be mixed. To pour the resin into the mould body, the spout shall be connected with the dome by turning for 180°. While turning, the membrane is cut open to pour the resin.

The Closed Mixing and Pouring System does provide resin handling without any skin contact.

For protection against pollution, a closure cap is applied onto the dome.

After curing, the remaining resin in the bag can be disposed as house waste.

Product Selection

Body Size	Application Range [mm ²]						
	 Cu		 AL				 ∅ mm
	4 x	5 x	4 x	5 x	4 x	5 x	
92-NBA 0	1.5 - 4	1.5 - 2.5	-	-	-	-	4 - 16
92-NBA 1	1.5 - 10	1.5 - 6	-	-	1.5 - 6	-	10 - 22
92-NBA 2	6 - 16	2.5 - 10	-	-	-	-	12 - 25
92-NBA 3	16 - 25	6 - 16	-	-	6 - 16	1.5 - 6	13 - 32
92-NBA 4	25 - 50	16 - 35	16 - 35	16 - 25	-	10 - 16	18 - 36
92-NBA 5	50 - 95	25 - 50	35 - 70	25 - 50	16 - 35	-	19 - 45
92-NBA 6	70 - 120	-	70 - 120	-	50 - 70	25 - 35	27 - 54
92-NBA 7	120 - 240	-	95 - 240	-	95 - 185	35 - 50	29 - 64

Type of Test according to EN50393 Table 3 / I / A1		Results
AC Voltage Withstand Test in air	4kV AC/ 1 min	passed
Insulation Resistance Test in air	1kV DC	> 10.000MΩ
Heat Cycle in air	63 cycles: 5h/3h	passed
Heat Cycle in water	63 cycles: 5h/3h	passed
AC Voltage Withstand Test in water	4 kV AC/ 1 min	passed
Insulation Resistance Test in water	1 kV DC	> 10.000MΩ

Testing

The full Scotchcast™ Resin Kit Series 92-NBA 0 up to 92-NBA 7 were tested according EN50393 Table 3 / I / A1.

Usage Information:

The resin will be supplied, in two-chamber plastic pouches with peelable barrier in the correct stoichiometric proportion. This type of packaging will assure the correct mixing ratio for applying the resin.

The packaging includes a Closed Mix and Pour Delivery System. The integrated pouring spout will be opened while attaching the mixed resin bag to the housing of the joint or by using the supplied opener.

For other information, relevant for the usage of the resin, like Gel-Time, Pot-Life, viscosity, density etc. please see the relevant Data Sheet.

Storage:

3M™ Scotchcast™ Resin 40 has a shelf life of at least 36 months when stored between 10°C and 40°C with a humidity level < 75 % in the originally sealed bag.

The expiration date of each product appears on the product label.

Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, it is the responsibility of the user to determine applicability of the resin.

Safety and Handling:

3M provides its customers with a product specific Material Safety Data Sheet (MSDS) to cover potential health effects, safe handling, storage, use and disposal information. 3M strongly encourages its customers to review the MSDS on its products prior to their use.

Product Stewardship:

3M has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis of our philosophy and policies by which we assess the health and environmental information on our products and then take the appropriate steps to protect employee, the public health and the environment.

Customer Notice:

3M encourages its customers and potential users of 3M products to review their applications for such products from the standpoint of human health and environmental quality. To help ensure that 3M products are not used in ways for which they were not intended or tested. 3M personnel are available to assist customers in dealing with ecological and product safety considerations. Your 3M sales representative can arrange for the proper contacts.

Regulatory Status:

The resin kit is in compliance with EU regulation 1907/2007/EC (REACH) and other European directives and regulations, relevant for this product, it is not in the scope of the European WEE and RoHS Directives.

3M and Scotchcast are trademarks of 3M Company.

Important Notice

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized office of the Seller.

The statements contained herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY; INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY; FOR ANY INJURY OR FOR ANY DIRECT; INDIRECT; INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS.