

PHILIPS

Lighting



Twistline Alu 3000 hours

Twistline Alu 3000h 50W GU10 230V 25D 1CT/10X5F

Mains-voltage long-life halogen burner in glass reflector. Ideal solution for small decorative luminaires, putting your objects in a superior-quality spot light. Aluminum coating prevents heat in the backlight.

Product data

General Information

Cap base	GU10 [GU10]
Philips code	18029
Bulb shape	MR16 [2inch/50mm]
Operating position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime (nom.)	3000 h
Switching cycle	12000X

Light Technical

Beam Angle (Nom)	25 °
Luminous flux (rated) (nom.)	385 lm
Luminous intensity (max.)	700 cd
Rated beam angle	25 °
Correlated colour temperature (nom.)	2800 K
Color rendering index (nom.)	100
LLMF at end of nominal lifetime (min.)	80 %
Luminous Flux In 90° Cone (Rated)	385 lm

Operating and Electrical

Power (Rated) (Nom)	50.0 W
Starting time (nom.)	0.0 s
Warm-up time to 60% light (nom.)	instant full light
Power factor (nom.)	1

Voltage (Nom)	230 V
---------------	-------

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Bulb finish	Clear (CL)
-------------	------------

Approval and Application


Energy efficiency label (EEL)	D
Energy Consumption kWh/1000 h	50 kWh

Product Data

Full product code	871150064932460
Order product name	Twistline Alu 3000h 50W GU10 230V 25D 1CT/10X5F
EAN/UPC – product	8711500649324
Order code	64932460
Numerator – quantity per pack	1
Numerator – packs per outer box	50
Material no. (12NC)	924880644264
Net weight (piece)	38.400 g
ILCOS Code	HAGS-50-230-GU10-51/25

Twistline Alu 3000 hours

Dimensional drawing



Product	D	C
Twistline Alu 3000h 50W GU10 230V 25D 1CT/10X5F	51 mm	51 mm

TWIST Alu 18029 50W GU10 230V 25D

