

# TRICKSTUFF

## Brake adaptor compatibility

by Sept. 2019

PM 6" fork / rear dropout						
	Rotor:	140 mm	160 mm	180 mm	200 mm	203 mm
IS brake with short arm		imp.	imp.	PM-IS+20	/	/
IS brake with long arm		imp.	imp.	imp.	PM-IS+20	/
PM brake		imp.	without ad.	PM-PM+20	PM-PM+40	PM-PM+43

PM 7" fork / rear dropout						
	Rotor:	140 mm	160 mm	180 mm	200 mm	203 mm
IS brake with short arm		imp.	imp.	imp.	PM-IS+20	/
IS brake with long arm		imp.	imp.	imp.	imp.	PM-IS+20
PM brake		imp.	imp.	without ad.	PM-PM+20	PM-PM+23

PM 8"						
	Rotor:	160 mm	180 mm	200 mm	203 mm	223 mm
IS brake with short arm		imp.	imp.	imp.	imp.	imp.
IS brake with long arm		imp.	imp.	imp.	imp.	imp.
PM brake		imp.	imp.	imp.	without ad.	PM-PM+20

<b>IS fork</b>					
<b>Rotor:</b>	<b>140 mm</b>	<b>160 mm</b>	<b>180 mm</b>	<b>200 mm</b>	<b>203 mm</b>
<b>IS brake with short arm</b>	imp.	without ad.	IS-IS+20	IS-IS+40	/
<b>IS brake with long arm</b>	imp.	imp.	without ad.	IS-IS+20	/
<b>PM brake</b>	imp.	IS-PM+0	IS-PM+20	IS-PM+40	IS-PM+43

<b>IS rear sockets (standard dimensions)</b>					
<b>Rotor:</b>	<b>140 mm</b>	<b>160 mm</b>	<b>180 mm</b>	<b>200 mm</b>	<b>203 mm</b>
<b>IS brake with short arm</b>	without ad.	IS-IS+20	IS-IS+40	/	/
<b>IS brake with long arm</b>	imp.	without ad.	IS-IS+20	IS-IS+40	/
<b>PM brake</b>	IS-PM+0	IS-PM+20	IS-PM+40	/	IS-PM+63

<b>Rock Shox Boxer until 09 (2010 and later have 6" PM)</b>					
<b>Rotor:</b>	<b>160 mm</b>	<b>180 mm</b>	<b>200 mm</b>	<b>203 mm</b>	
<b>IS brake with short arm</b>	imp.	Box+20	Box+40	/	
<b>IS brake with long arm</b>	imp.	imp.	Box+20	/	
<b>PM brake</b>	/	/	/	Box-PM+43	

<b>Fox 40 until 2013 (IS-DH-8")</b>					
<b>Rotor:</b>	<b>160 mm</b>	<b>180 mm</b>	<b>200 mm</b>	<b>203 mm</b>	<b>223 mm</b>
<b>IS brake with short arm</b>	imp.	imp.	imp.	without ad.	imp.
<b>IS brake with long arm</b>	imp.	imp.	imp.	imp.	without ad.
<b>CLEG Fox40</b>	imp.	imp.	without ad.	imp.	imp.
<b>PM brake</b>	imp.	imp.	imp.	IS-PM+0	IS-PM+20

**imp.:** Combination impossible

**IS:** IS2000 Standard

**ohne Ad.:** Direct mount without adapter

**PM:** Postmount Standard

**/:** adapter not available at Trickstuff

**"IS brake with short arm":** all IS brake calipers, which are designed as front brakes with 160 mm rotors or as rear brakes with 140mm rotors.

**"IS brake with long arm":** all IS brake calipers, which are designed as front brakes with 180 mm rotors or as rear brakes with 160mm rotors.

(without adapter; example: former Magura Louise FR)